



DYSIN
AUTOMOBILES




SINOTRUK

HOWO NX 240 HP



BUILT TO DELIVER.



FUEL EFFICIENT
PERFORMANCE



HIGH-LOW
TRANSMISSION



LUXURIOUS AC
CABIN



LOWER
OPERATING COST



PARAMETERS	240 4x2	240 6x2	240 6x2
	Prime Mover	Prime Mover	Rigid Truck
Brand	HOWO	HOWO	HOWO
Emission	EURO II	EURO II	EURO II
Driving Type	4x2	6x2	6x2
ENGINE			
Model Configuration	YC6A240-33	YC6A240-33	YC6A240-33
Configuration	6 in-line	6 in-line	6 in-line
Type	Diesel, 6 Cylinder	Diesel, 6 Cylinder	Diesel, 6 Cylinder
Max. Torque (N.m/rpm)	950 Nm / 1200–1700 rpm	950 Nm / 1200–1700 rpm	950 Nm / 1200–1700 rpm
Rated Power (kW/rpm)	177 kW / 2300 rpm	177 kW / 2300 rpm	177 kW / 2300 rpm
ELECTRICAL SYSTEM			
Operational Voltage	24V, Negative Grounding	24V, Negative Grounding	24V, Negative Grounding
Starter	6 kW / 8.5 kW	6kW / 8.5 kW	6 kW / 8.5 kW
Battery (V/Ah)	2×12V, 165Ah	2×12V, 165Ah	2×12V, 165Ah
TRANSMISSION			
Model	8JS118T	8JS118T	8JS118T
No. of Gears	8 Forward, 2 Reverse	8 Forward, 2 Reverse	8 Forward, 2 Reverse
Type	High-Low	High-Low	High-Low
AXLE / FUEL TANK			
Front Axle	5.5 Ton Forging I-beam Front Axle	5.5 Ton Forging I-beam Front Axle	5.5 Ton Forging I-beam Front Axle
Real Axle	13 Ton Central Single Reduction	13x2 Ton Central Single Reduction	13x2 Ton Central Single Reduction
Fuel Tank	400 L	400 L	400 L
CLUTCH, STEERING & TYRE			
Steering Model	Hydraulically Assisted	Hydraulically Assisted	Hydraulically Assisted
Clutch Size	430 mm (17 inch) Diaphragm Spring Clutch	430 mm (17 inch) Diaphragm Spring Clutch	430 mm (17 inch) Diaphragm Spring Clutch
Tyres	11.00R20	11.00R20	11.00R20
WEIGHT			
Gross Combination Weight	41,000 kg	58,500 kg	28,500 kg
Kerb Mass	5,910 kg	7,690 kg	7,900 kg
BRAKE SYSTEM			
Service Brake	Dual Circuit Air Brake	Dual Circuit Air Brake	Dual Circuit Air Brake
Parking Brake	Spring Energy, Compressed Air Operating on Rear Wheels	Spring Energy, Compressed Air Operating on Rear Wheels	Spring Energy, Compressed Air Operating on Rear Wheels
Auxiliary Brake	Exhaust Valve Brake	Exhaust Valve Brake	Exhaust Valve Brake
Brake System	ABS	ABS	ABS
DIMENSIONS			
Overall Dimensions (L x W x H) (mm)	6045 × 2550 × 3100 mm	6935 × 2550 × 3100 mm	9500 × 2550 × 3100 mm
Wheel Base (mm)	3600 mm	3300 + 1350 mm	4350 + 1350 mm
Min. Ground Clearance (mm)	267 mm	273 mm	262 mm
Front Overhang (mm)	1550 mm	1550 mm	1550 mm
Rear Overhang (mm)	895 mm	735 mm	2250 mm

Note: Specifications are subjected to change without prior notice.

ADDRESSES

Head Office: 310-Fairy Meadows Lane,
West Canal Bank Road, Lahore.

- **Phone:** 042 35299227
- **Fax:** 042 35298242

Regional Office South: Plot No 221-F,
P.E.C.H.S, Block 2, Karachi

- Phone: 021-34546427

Regional Office South Punjab:
Bahawalpur Bypass Road, Near Total
Petrol Pump, Multan

Regional Office North: 421/C, Avenue 1
Street 1, Westridge-1, Near Chur Chowk,
Peshawar Road, Rawalpindi

- Phone: 051 5493604

Plant Address: Plot # 35, Block-M, Hub
Industrial Estate, Lasbela Balochistan-
Pakistan



Scan to know
more about DYSIN

 **0301-DYSIN-66**
0301 3974 666

 **www.dysin.com.pk**

 **info@dysin.com.pk**